

Rec'd PCT/PTO 21 JAN 2005



PG/EP 03 / 07065



INVESTOR IN PEOPLE

10/521983

REC'D 26 AUG 2003

WIPO

PCT


The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

*R. Mahoney*

Dated 11 June 2003

BEST AVAILABLE COPY

**PRIORITY  
DOCUMENT**

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)



The  
Patent  
Office

PC1/EP 03707065

25JUL02 E736007-6 D02898  
P01/7700 0.00 P02898 Office

# Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

24 JUL 2002

Cardiff Road  
Newport  
Gwent NP10 8QQ

1. Your reference

J3681(C)/ijh

0217256.7

2. Patent application number  
(The Patent Office will fill in this part)

3. Full name, address and postcode of the or of each applicant (underline all surnames)

UNILEVER PLC  
UNILEVER HOUSE, BLACKFRIARS  
LONDON, EC4P 4BQ

Patents ADP number (if you know it)

1628002

If the applicant is a corporate body, give the country/state of its incorporation

UNITED KINGDOM

4. Title of the invention

ANTIPERSPIRANT AEROSOL COMPOSITIONS

5. Name of your agent (if you have one)

ELLIOTT, Peter William

"Address for Service" in the United Kingdom to which all correspondence should be sent (including the postcode)

PATENT DEPARTMENT, UNILEVER PLC  
COLWORTH HOUSE, SHARNBROOK  
BEDFORD, MK44 1LQ

Patents ADP number (if you know it)

1628003

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country	Priority application number (if you know it)	Date of filing (day / month / year)
---------	---	--

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application	Date of filing (day/month/year)
-------------------------------	------------------------------------

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

YES

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body. See note (d))

**Patents Form 1/77**

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description	12 /
Claim(s)	3 /
Abstract	1 /
Drawing(s)	1 + 1 RN

10. If you are also filing any of the following, state how many against each item.

Priority Documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*) 1

Request for substantive examination (*Patents Form 10/77*)

Any other documents  
(please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature(s)



Date: 24/07/02

Sandra Jane EDWARDS, Authorised Signatory

12. Name and daytime telephone number of person to contact in the United Kingdom

Isobel Howell, Tel 01234 22 2082

**Warning**

*After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.*

**Notes**

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay please contact the Patent Office.*

- 1 -

ANTIPERSPIRANT AEROSOL COMPOSITIONS

This invention relates to antiperspirant aerosol  
5 compositions suitable for topical application to the human  
body and to methods of making the same.

Antiperspirant compositions suitable for topical application  
typically comprise an antiperspirant material such as  
10 aluminium chlorohydrate which acts to suppress the level of  
perspiration on the area of the body to which it is applied.  
Antiperspirant compositions are widely applied in the form  
of a pressurised, propellant driven aerosol spray.

15 Aerosol antiperspirant compositions typically have the  
antiperspirant material suspended in an anhydrous carrier  
fluid, together with a propellant and a suspending agent.  
Other minor ingredients can also be present, and the  
composition is housed in a pressurised container.

20 A major problem associated with all antiperspirants,  
including aerosol antiperspirants, is that of deposition or  
whitening where the antiperspirant active, which is usually  
in powder form, is deposited on a user's clothes or skin,  
25 thereby causing visible whitening/staining and occasionally  
damage to the clothes.

Various attempts have been made to reduce the whitening or  
visible deposits. A widely used approach has been to  
30 incorporate a masking oil such as an aliphatic hydrocarbon,

ester oil, or silicone fluid into antiperspirant formulations.

5 The masking oil functions by coating the surface of the antiperspirant active particles and minimises the scattering of light, thereby rendering the active less visible to the naked eye.

10 The masking method has been found to reduce whitening in stick and roll-on products. The reduction of whitening caused by aerosol compositions containing activated aluminium chlorohydrate (AACH) as the active is more difficult. This is in part due to the difficulty in matching the refractive index (RI) of the masking oil with  
15 that of AACH, as commercially available AACH does not have a continuous RI value throughout the particle. More particularly, AACH particles generally contain hollow cores, having an RI of 1.0 while the RI of the outer particle is in the region of 1.5 which results in visible whitening.

20

One approach to reducing the whitening problem with AACH aerosol compositions is described in US 5,840,289 (Hall), wherein the AACH is milled to reduce the number of particles having hollow cores and the resulting active is masked with  
25 a masking oil of appropriate RI.

The applicants have now discovered that good antiperspirancy and remarkably low whitening can be achieved with AACH aerosol compositions comprising milled AACH having non-  
30 hollow particles in combination with a masking oil of particularly high viscosity.

Thus, according to a first aspect of the invention, there is provided a suspension antiperspirant aerosol' composition comprising milled activated aluminium chlorohydrate having non-hollow particles and a carrier fluid comprising a  
5 masking oil of viscosity  $10^3 \text{ mm}^2/\text{s}$  or greater.

According to a second aspect of the invention, there is provided a method of manufacture of a suspension antiperspirant aerosol composition, said method comprising  
10 the suspension of a milled activated aluminium chlorohydrate (AACH) having non-hollow particles in a carrier fluid comprising a masking oil of viscosity  $10^3 \text{ mm}^2/\text{s}$  or greater.

According to a third aspect of the invention, there is  
15 provided a method of reducing perspiration and giving low visible deposits comprising the application to the human body of a suspension antiperspirant aerosol composition comprising milled AACH having non-hollow particles and a carrier fluid comprising a masking oil of viscosity  $10^3$   
20  $\text{mm}^2/\text{s}$  or greater.

Without wishing to be bound by theory, the applicant believes that the reduced white deposits obtained with antiperspirant compositions of the present invention is due  
25 to the particular morphology of the antiperspirant actives selected and their highly effective coating by the particularly high viscosity masking oils indicated.

The chemical nature and preparation of AACH antiperspirant  
30 actives suitable for use in the present invention are

described in GB 1,568,831, GB 1,597,497, GB 1,597,498, EP 6,738, EP 6,739, EP 7,191, EP 191,628, EP 256,832 and EP 491,395, the contents of which are incorporated herein by reference. The amount of AACH present in the compositions of the invention may be from 1 to 30% and particularly from 2 to 20%, the upper level of AACH preferably being 10% or less and especially being 5% or less, all percentages being by weight of the composition.

10 The AACH used in the present invention is milled and has non-hollow particles. Preferably, a high level of non-hollow AACH particulate material is present, the hollows in the particles comprising less than 40% of the total volume of the AACH. It is particularly preferred that the hollows  
15 comprise less than 20%, and especially less than 10%, of the total volume of the AACH. AACH in which hollows comprise less than 5% of the total volume of the active is most preferred. Measurement of the amount of non-hollow AACH particulate material may be performed by a suitable  
20 microscopy technique (e.g. SEM) in combination with suitable image analysis.

Suitably, the AACH used in the present invention has a continuous RI. The RI of the AACH is preferably between  
25 1.52 to 1.57. The mean particle size of the AACH is preferably from 20 to 30 microns (measured as the D[4,3], using a light scattering technique). Typically the AACH is prepared by milling a sample having a mean particle size (measured as above) of from 50 to 150 micron and comprising  
30 hollow particles.

The masking oil used in the present invention has a particularly high viscosity, being of viscosity  $10^3$  mm<sup>2</sup>/s or greater. The viscosity values quoted in this specification are kinematic viscosities, measured at 25°C. A suitable method for measuring kinematic viscosities utilises a glass capillary viscometer, for example, as described in Dow Corning's Corporate Test Method CTM 0004, of July 29, 1970.

The masking oil may be any suitable oil of appropriate viscosity, examples including hydrocarbon oils, ester oils, and silicone oils. Suitable hydrocarbon oils include hydrogenated polyolefins, in particular hydrogenated polydecenes, examples including Puresyn oils of viscosity  $10^3$  mm<sup>2</sup>/s or greater, available from Mobil. Suitable silicone oils include linear and crosslinked polydimethylsiloxane (PDMS) fluids, examples including the DC200 PDMS fluids of viscosity  $10^3$  mm<sup>2</sup>/s or greater; available from Dow Corning.

The RI of the masking oil is preferably from 1.40 to 1.57. Silicone oils are particularly preferred. The viscosity of the masking is  $10^3$  mm<sup>2</sup>/s or greater, preferably  $10^4$  mm<sup>2</sup>/s or greater, and more preferably 30,000 mm<sup>2</sup>/s or greater.

The masking oil may be used in an amount from 0.5% or 1%, up to 30%, in particular up to 10%, and especially up to 5%, all percentages being by weight of the total composition.



The masking oil may function as an emollient oil and/or lubricant. It may also serve to facilitate uniform distribution of the antiperspirant material on the skin.

- 5 Additional emollient oils may also be present in the carrier fluid. Suitable emollient oils are disclosed in US Patent Nos. 4,822,596 and 4,904,463, the disclosures of which are incorporated by reference herein. Preferred emollient oils are the Finsolv (Trade Mark) benzoate esters available from
- 10 Finetex Inc.; Panalane, a hydrogenated polybutene, available from Amoco; Fluid AP (PPG-14 butylether), available from Union Carbide; isopropyl palmitate; phenylsilicone; and isopropyl myristate.
- 15 It is particularly preferred that the carrier fluid comprises a volatile silicone fluid. Preferred volatile fluids include dimethyl cyclosiloxanes, such Dow Corning fluids DC244, DC245, DC344 and DC345. Typically such materials are present at a level of from 1 to 30%, in
- 20 particular from 2 to 20%, and especially from 5 to 10% by weight of the composition.

- In order to prevent caking or settling out of the antiperspirant salt from the carrier fluid, a bulking or
- 25 suspending agent is preferably incorporated into the composition of the invention. The suspending agent is preferably hydrophobically treated montmorillonite clay such as a bentonite or a hectorite. One such commercially available clay is Bentone 38V, which is a hectorite clay
- 30 available from NL Industries, Inc. The amount of clay in

the composition of the invention may be from 0.2 to 5.0% by weight of the total composition.

A propellant gas is generally present as part of the compositions of the invention. Any liquefiable gas known in the art for use in propellant driven aerosol products may be used. Examples of suitable propellants include trichlorofluoromethane, trichlorotrifluoromethane, difluoroethane, propane, butane or isobutane or combinations thereof. When used, the amount of liquefied gas in the composition of the invention is typically from 5 to 95% and preferably from 30 to 90% by weight of the composition. Alternatively, compressed gas such as air, nitrogen, or carbon dioxide may be used as propellant.

15

Other minor ingredients which may be present in the compositions of the invention include:

- cosmetically acceptable carrier fluid components, such as straight and branched chain alcohols, for example, ethanol, isobutanol or isopropanol;
- deodorant active perfumes and deodorant compounds which can act as antimicrobial agents;
- hydrophobic oils, such as liquid paraffin oils;
- inorganic electrolytes, such as sodium chloride or sodium sulphate;
- other thickeners such as clays, silicas, for example, Aerosil 200 and hydroxypropyl celluloses such as Klucel;
- polar additives such as propylene carbonate or alcohol;
- skin feel improvers, such as talc and finely divided polyethylene such as Accumist B18;
- humectants, such as polyols, for example glycerol;

30

- perfumes;
  - preservatives and antioxidants;
  - skin benefit agents such as allantoin;
  - colours;
- 5 - other cosmetic adjuncts conventionally employed in propellant driven aerosol products.

The compositions of the invention may be manufactured by a method comprising the suspension of a milled activated  
10 aluminium chlorohydrate (AACH) having non-hollow particles in a carrier fluid comprising a masking oil of viscosity  $10^3$  mm<sup>2</sup>/s or greater. Techniques employed in the manufacture of conventional suspension AP aerosol products may be employed. In a particular method of manufacture, the AACH is suspended  
15 in a pre-formed mixture comprising volatile silicone, masking oil, and perfume, and said suspension is then placed in an aerosol can, preferably made of aluminium or tinfoil, and a propellant gas is added in a liquefied form.

20

### Examples

The compositions indicated in the Tables below were prepared in the following manner. The volatile silicone, other oil  
25 (silicone oil or hydrocarbon oil), and Bentone 38V were sheared together at 9000 rpm for 5 minutes using a Silverson L4RT mixer. The perfume was then added whilst shearing and shearing was continued for a further 2 minutes. Shearing was then discontinued and the AACH was dispersed in the

mixture using a spatula. The mixture was then subjected to a further 5 minutes shearing using the Silverson L4RT mixer.

The whiteness scores were obtained using the following method. The fully formulated compositions were each sprayed directly onto black test cloths from a distance of 25 cm, using a standard spray nozzle and a duration of 5 seconds per cloth. After approximately one hour, the whiteness scores of the cloths were measured using an image analysis technique. The results were analysed using standard statistical techniques to give the average whiteness score from each composition and the 95% confidence limits.

Comparative examples are indicated by letter codes.

Compositional amounts are given as percentages by weight.

Table 1: Compositions comprising 3% masking oil

	Examples			
	A	B	C	1
Components				
A296 <sup>1</sup>	2	2	-	-
Alloxicol LR <sup>2</sup>	-	-	2	2
Bentone 38V <sup>3</sup>	0.5	0.5	0.5	0.5
Volatile silicone <sup>4</sup>	6.9	6.9	6.9	6.9
DC 200 (50) <sup>5</sup>	3	-	3	-
DC 200 (30,000) <sup>6</sup>	-	3	-	3
Fragrance	0.6	0.6	0.6	0.6
CAP 40 <sup>7</sup>	87	87	87	87
Whiteness				
Score:	1789	1397	1420	750
95% limits:	±145	±89	±64	±57

- 10 -

1. Conventional unmilled AACH, ex BK Giulini.
  2. Milled AACH, ex BK Giulini.
  3. Suspending agent, hectorite clay, ex NL Industries.
  4. DC245, ex Dow Corning.
  - 5 5. PDMS of viscosity 50 mm<sup>2</sup>/s, ex Dow Corning.
  6. PDMS of viscosity 30,000 mm<sup>2</sup>/s, ex Dow Corning.
  7. Propellant, proprietary mix of butane, isobutane and propane, ex. Calor.
- 10 These results illustrate that use of a milled active having non-hollow particles (Alloxicol LR) and a masking oil having a particularly high viscosity (DC 200 (30,000)) leads to a particularly low whiteness score (Example 1). Poorer (i.e. higher) whiteness scores were obtained when the composition
- 15 comprised only one of the required features (Examples B and C) and an even poorer whiteness score was obtained when the composition comprised neither of the required features (Example A).

Table 2: Compositions comprising 1% masking oil

	Examples			
	D	2	3	4
Components				
Alloxicol LR <sup>1</sup>	2	2	2	2
Bentone 38V <sup>1</sup>	0.5	0.5	0.5	0.5
Volatile silicone <sup>1</sup>	8.9 <sup>2</sup>	8.9	8.9	8.9
DC 200 (50) <sup>1</sup>	1	-	-	-
DC 200 (1000) <sup>3</sup>	-	1	-	-
DC 200 (30,000) <sup>1</sup>	-	-	1	-
Puresyn 1000 <sup>4</sup>	-	-		1
Fragrance	0.6	0.6	0.6	0.6
CAP 40 <sup>1</sup>	87	87	87	87
Whiteness				
Score:	1429	1213	848	1064
95% limits:	±123	±210	±35	±8

1. As defined in Table 1.

5 2. Including a small amount of silicone gum (Q2-1501, ex Dow Corning).

3. PDMS of viscosity 1,000 mm<sup>2</sup>/s, ex Dow Corning.

4. Hydrogenated polydecene of viscosity 42,300 mm<sup>2</sup>/s, ex Mobil.

10


These results illustrate the benefit of using a masking oil of viscosity 10<sup>3</sup> mm<sup>2</sup>/s or greater, whether the masking oil be a silicone oil or a hydrocarbon oil.

15 The results from silicone oil containing Examples D, 2, and 3 are shown again in Figure 1, which suggests that a

- 12 -

logarithmic-linear relationship between viscosity and  
whiteness score may be present.

Figure 1: relationship between PDMS viscosity and whiteness score



5

10

15



CLAIMS

1. A suspension antiperspirant aerosol composition comprising milled activated aluminium chlorohydrate (AACH) having non-hollow particles and a carrier fluid comprising a masking oil of viscosity  $10^3 \text{ mm}^2/\text{s}$  or greater.  
5
2. An aerosol composition according to claim 1, wherein the AACH is present at a level of from 1% to 30% by weight of the composition.  
10
3. An aerosol composition according to claim 2 wherein the AACH is present at a level of from 2% to 5% by weight of the composition.  
15
4. An aerosol composition according to any of the preceding claims, wherein the masking oil has a viscosity of  $30,000 \text{ mm}^2/\text{s}$  or greater.  
20
5. An aerosol composition according to any of the preceding claims, wherein the AACH has a continuous RI.
6. An aerosol composition according to any of the preceding claims, wherein the masking oil has an RI of 1.40 to 1.57.  
25
8. An aerosol composition according to claim 6, wherein the masking oil is a silicone oil.  
30

- 15 -

9. An aerosol composition according to any of the preceding claims, comprising an additional emollient oil.

5 10. An aerosol composition according to any of the preceding claims, comprising a bulking or suspending agent.

10 11. An aerosol composition according to any of the preceding claims, comprising a volatile silicone.

12. An aerosol composition according to any of the preceding claims, comprising a propellant gas.

15 13. An aerosol composition according to claim 12, wherein the propellant gas is a liquefied gas at a level of from 5 to 95% by weight of the composition.

20 14. A method of manufacture of a suspension antiperspirant aerosol composition, said method comprising the suspension of a milled activated aluminium chlorohydrate (AACH) having non-hollow particles in a carrier fluid comprising a masking oil of viscosity  $10^3$  mm<sup>2</sup>/s or greater.

25

15. A method of reducing perspiration and giving low visible deposits comprising the application to the human body of a suspension antiperspirant aerosol composition comprising milled AACH having non-hollow

30

- 16 -

particles and a carrier fluid comprising a masking oil of viscosity  $10^3$  mm<sup>2</sup>/s or greater.

- 17 -

ABSTRACT

- 5 A suspension antiperspirant aerosol composition comprising milled activated aluminium chlorohydrate (AACH) having non-hollow particles and a carrier fluid comprising a masking oil of viscosity  $10^3 \text{ mm}^2/\text{s}$  or greater gives good antiperspirancy and reduced levels of white deposits.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**